

In the Claims:

Please amend the claims as follows.

1. (Currently Amended) A process for the catalytic selective oxidation of a sulfur compounds contained in a hydrocarbonaceous feedstock to sulfur dioxide, wherein the process comprises the steps of: contacting a gaseous feed mixture of the hydrocarbonaceous feedstock, of which the sulfur compound is selected from the group consisting of hydrogen sulfide, mercaptans, disulfides, and heterocyclic sulfur compounds, and a molecular-oxygen containing gas with a catalyst at a temperature of at most 500 °C, wherein said catalyst comprises a catalytically active group VIII noble metal selected from the group consisting of platinum, rhodium, iridium and combinations of two or more thereof at a concentration in the range of from 0.02 to 10% by weight, based on the total weight of the catalyst, supported on a catalyst carrier comprising stabilized or partially stabilized zirconia, wherein said feed mixture has an having oxygen-to-carbon ratio of below 0.15.
2. (Original) The process of claim 1 wherein the oxygen-to-carbon ratio of the feed mixture is below 0.10.

Claims 3-8 (Canceled).

9. (Currently Amended) The process of claim 4~~2~~ wherein the temperature is maintained in the range of from 200 to 500°C.

Claim 10 (Canceled).

11. (Original) The process of claim 1 wherein the feed mixture is contacted with the catalyst at a pressure in the range of from 1 to 10 bar (absolute).
12. (Original) The process of claim 11 wherein the feed mixture is contacted with the catalyst at a pressure in the range of from of from 1 to 5 bar (absolute).
13. (Original) The process of claim 1 wherein the feed mixture is contacted with the catalyst at ambient pressure.
14. (Original) The process of claim 1 wherein the hydrocarbonaceous feedstock is a gaseous hydrocarbonaceous feedstock.
15. (Original) The process of claim 14 wherein the hydrocarbonaceous feedstock is methane or natural gas.
16. (Original) The process of claim 14 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 10% v/v.

17. (Original) The process of claim 16 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 5% v/v.

18. (Original) The process of claim 15 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 10% v/v.

19. (Original) The process of claim 18 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 5% v/v.

20. (Original) The process of claim 1 wherein the feedstock is a liquid hydrocarbonaceous feedstock containing at most 1000 ppmw sulfur.

21. (Currently Amended) A process for the catalytic selective oxidation of ~~sulfur compounds~~ hydrogen sulfide contained in a methane or natural gas feedstock to sulfur dioxide, wherein the process comprises the steps of: contacting a gaseous feed mixture of the methane or natural gas feedstock and a molecular-oxygen containing gas, wherein the gaseous feed mixture comprises up to 10% v/v hydrogen sulfide, with a catalyst at a temperature of at most 500 °C, wherein said catalyst comprises a catalytically active group VIII noble metal selected from the group consisting of platinum, rhodium, iridium and combinations of two or more thereof at a concentration in the range of from 0.02 to 10% by weight, based on the total weight of the catalyst, supported on a refractory oxide comprising stabilized or partially stabilized zirconia, wherein said feed mixture has an ~~having~~ oxygen-to-carbon ratio of below 0.15.

Claims 22-23 (Canceled).

24. (Currently Amended) The process of claim ~~23~~21 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 5% v/v.

25. (Currently Amended) A process for the desulfurization of a hydrocarbonaceous feedstock, wherein the process comprises the steps of: contacting a gaseous feed mixture of the hydrocarbonaceous feedstock, which contains a sulfur compound selected from the group consisting of hydrogen sulfide, mercaptans, disulfides, and heterocyclic sulfur compounds, and a molecular-oxygen containing gas with a catalyst at a temperature of at most 500 °C, wherein said catalyst comprises a catalytically active group VIII noble metal selected from the group consisting of platinum, rhodium, iridium and combinations of two or more thereof at a concentration in the range of from 0.02 to 10% by weight, based on the total weight of the catalyst, supported on a refractory oxide catalyst carrier comprising partially stabilized or stabilized zirconia, wherein said gaseous feed mixture has an ~~having~~ oxygen-to-carbon ratio of below 0.15, thereby selectively oxidizing the sulfur compounds in the hydrocarbonaceous feedstock to sulfur dioxide; and removing the thus-formed sulfur dioxide from the hydrocarbonaceous feedstock.

26. (Currently Amended) The process of claim 25 wherein the oxygen-to-carbon ratio of the gaseous feed mixture is below 0.10.

Claims 27-29 (Canceled).

30. (Currently Amended) The process of claim ~~29~~26 wherein the oxygen-to-carbon ratio of the gaseous feed mixture is below 0.10.

Claims 31-32 (Canceled).

33. (Original) The process of claim 25 wherein the temperature is maintained in the range of from 200 to 500°C.

34. (Original) The process of claim 25 wherein the temperature is maintained in the range of from 200 to 300°C.

35. (Currently Amended) The process of claim 25 wherein the gaseous feed mixture is contacted with the catalyst at a pressure in the range of from 1 to 10 bar (absolute).

36. (Currently Amended) The process of claim 35 wherein the gaseous feed mixture is contacted with the catalyst at a pressure in the range of from 1 to 5 bar (absolute).

37. (Currently Amended) The process of claim 25 wherein the gaseous feed mixture is contacted with the catalyst at ambient pressure.

38. (Original) The process of claim 25 wherein the hydrocarbonaceous feedstock is a gaseous hydrocarbonaceous feedstock.

39. (Original) The process of claim 38 wherein the hydrocarbonaceous feedstock is methane or natural gas.

40. (Original) The process of claim 38 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 10% v/v.

41. (Original) The process of claim 40 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 5% v/v.

42. (Original) The process of claim 39 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 10% v/v.

43. (Original) The process of claim 42 wherein the hydrocarbonaceous feedstock comprises hydrogen sulfide in a concentration of at most 5% v/v.

44. (Original) The process of claim 25 wherein the feedstock is a liquid hydrocarbonaceous feedstock containing at most 1000 ppmw sulfur.